

# Grauwasser Recycling System, 250 l/d

## Greywater Recycling System, 250 l/d

GWO 1.0-250, outdoor



Technisches Datenblatt / technical data

Kapazität		capacity
Gesamtvolumen Stufe 1	950 l	total volume stage 1
Gesamtvolumen Stufe 2	900 l	total volume stage 2
Tagesfiltrationsleistung	<b>250 l</b>	daily filtration capacity
DEA Klarwasserdruckpumpe X1000		submersible pump X1000
max. Förderstrom Betriebswasser	5,4 m³/h	max flowrate service water
max. Betriebsdruck Betriebswasser	3,6 bar	max. operating pressure service water
Motorleistung	900 W	performance

Anschlüsse		connections
Trinkwasser-Nachspeisung	3/4"	potable water back-up
Betriebswasser	1"	service water
Zulauf in die Anlage	DN 100	input to unit
Überlauf in Kanalisation	DN 100	overflow to sewage

Aufstellraum muss ausreichend belüftet und mit Bodenablauf versehen sein.

Working room needs to be airventilated, floor drain necessary.

Steuerung		control unit
Zeitintervalle für Belegung, Filtration vorprogrammiert*		time interval for aeration, filtration pre-programmed*
Abmessungen (B x H x T)	400 x 500 x 200 mm	measurements (W x H x D)
* Anpassung bedarfsseitig möglich		* possible adjustment according demand

Trinkwassernachspeisung		main water supply
Magnetablaufventil 1" (optional, größer möglich)		solenoid valve 1" (optional, bigger sizes available)

Netzanschluss		electric main supply
Spannung	230 V / 50 Hz	voltage
Absicherung	bauseitig / by customer	fuse

Gewicht, Maße, Farbe		weight, measurements, colour
Leergewicht, Anlage	150 kg	weight empty
max. Gesamtgewicht im Betrieb		unit working (max. weight)
Tank Filtration	Ø 800, H 2.150 mm	filtration tank
Farbe	schwarz / black	colour
Volumen	1x 950 l	volume
Tank Betriebswasser	Ø 800, H 2.150 mm	service water tank
Farbe	schwarz / black	colour
Volumen	1x 950 l	volume

Trinkwassernachspeisung	inklusive / inclusive	drinking water feed
Betriebswasseranschluss	inklusive / inclusive	service water connection

[www.greenlife.de](http://www.greenlife.de)

# Grauwasser Recycling System, 250 l/d

## Greywater Recycling System, 250 l/d

GWO 1.0-250, outdoor



The **GreenLife greywater-recycling-system GWO 1.0-250** has a daily greywater filtration capacity of up to 250 liters.

The **greywater-recycling-systems of GreenLife** are configured for the treatment of greywater, i.e. low polluted waste water from personal hygiene (shower, bath tub, hand washbasin). The applied BioMembranefilter-technology assures the complete separation of the biomass from the cleaned greywater. The clearwater is free from solids and a complete blocking of bacteria and germs, with a blocking rate of 99,9999%, guaranteed. The total recycling process is composed of the biological treatment, the ultrafiltration (MBR-Membrane bio-reactor) and will be stored after it in the clearwater tank. The result is clear germ free service water (non-potable) available for reuse in WC's, cleaning purposes, garden irrigation and/or industrial applications!

### results:

The quality of the service water (non-potable) fulfills the requirements of the European (EU) guidelines for bathing water 76/160/EEC and 2006/7/EC and DIN 19650, class 2.

### consisting of:

- 1 filtration tank** incl.:  
greywater inflow, membrane filter and filtrate box, filtrate pump, negative buoyancy, cable and hose bushings,
- 2 service water tank** incl.:  
filtrate access, connection drinking water feed unit (optional), connection twin pump station (optional)
- 3 control unit** incl.:  
stainless steel bracket, aeration pump, control module, cable and connecting plug (completely programmed and pre-assembled),



